

(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 805 591 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
05.11.1997 Bulletin 1997/45

(51) Int. Cl.⁶: **H04N 7/12**

(21) Application number: **97107041.2**

(22) Date of filing: **29.04.1997**

(84) Designated Contracting States:
DE FR GB

(30) Priority: **02.05.1996 JP 111676/96**
28.01.1997 JP 13637/97

(71) Applicant:
MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.
Kadoma-shi, Osaka 571 (JP)

(72) Inventors:

- **Aoki, Norio**
Hirakatashi, Koganeno 2-16-5, 573 (JP)
- **Yoneda, Yasushi**
Ikedashi, Fushiodai 2-9-1 2-193, 563 (JP)

(74) Representative: **Kügele, Bernhard et al**
NOVAPAT INTERNATIONAL SA,
9, Rue du Valais
1202 Genève (CH)

(54) **Apparatus for transmitting television broadcasting program and apparatus for receiving television broadcasting program**

(57) An apparatus for transmitting a TV broadcasting program comprises a video image synthesizer for synthesizing video images so that the video images of a plurality of channels for promotion are displayed on a screen by screen division; an encoder for digitally encoding the synthesized one video image or more; and a multiplexer for multiplexing and outputting the digitalized video images for promotion and digitally encoded programs of normal channels.

EP 0 805 591 A2

Description

FIELD OF THE INVENTION

The present invention relates to an apparatus for transmitting a TV broadcasting program and an apparatus for receiving a TV broadcasting program and, more particularly to one which has a display format of an electronic program guide for displaying TV program information on a monitor with improved degree of freedom.

BACKGROUND OF THE INVENTION

Conventionally, in a TV receiver in analog form broadcasted at home, a viewer chooses a broadcasting station by choosing a channel of a program which the viewer demands, referring to programs described in a newspaper or a magazine. However, when a program is suddenly changed due to interruption of a temporary program or the like, the viewer cannot see a desired program. In view of this, for example, as described in Japanese Patent Application No. 5-84479, TV program information is transmitted utilizing character broadcasting and the TV program information is analyzed to display a TV program table on the monitor in a receiver. Some cable TVs or the like provide an electronic program guide (EPG) service in which a screen of each program is miniaturized as a motion picture and a plurality of segments of the miniaturized screen is disposed on a screen and transmitted through a channel. Thanks to this service, conveniently, the viewer can utilize the latest program information using not characters but video images.

In the conventional apparatus for transmitting a TV broadcasting program and apparatus for receiving a TV broadcasting program constructed described above, a program content of each program can be referred to on the monitor through a dedicated EPG channel. However, a video image for the EPG channel is produced by editing a program content of each program in a broadcasting station. Therefore, the viewer cannot dispose and refer to a video image of a desired program in an arbitrary position on the plurality of segmented screens, so that the viewer can only refer to the EPG in a prescribed format created in the broadcasting station.

In recent years, broadcasting in digital system has been developed in place of broadcasting in analog system. Attention has been paid to the digital system, since it can provide various services which the analog system cannot realize. The digital system can provide several tens to several hundreds of channels as programs, so that the EPG service becomes important. However, in the existing EPG service system described above, since only an edition of many programs performed by the broadcasting station is received, the viewer has too many alternatives to choose a program, leading to a problematic situation such as complicated choice of programs.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an apparatus for transmitting a TV broadcasting program and an apparatus for receiving a TV broadcasting program, which can change and customize a layout or the like when the viewer refers to the EPG, making the best use of advantages of digital broadcasting.

Other objects and advantages of the present invention will become apparent from the detailed description given hereinafter. It should be understood, however, that the detailed description and specific embodiment are given by way of illustration only, since various changes and modifications within the scope of the invention will appear to those skilled in the art from this detailed description.

According to a first aspect of the present invention, an apparatus for transmitting a TV broadcasting program comprises a video image synthesizer for synthesizing video images so that video images of programs of a plurality of channels for promotion are displayed on a screen by screen division, an encoder for digitally encoding the synthesized one video image or more, and a multiplexer for multiplexing and outputting the digitalized video images for promotion and digitally encoded programs of normal channels.

According to a second aspect of the present invention, an apparatus for transmitting a TV broadcasting program comprises a multiplexer for time-dividing video images of programs of a plurality of channels for promotion, multiplexing and outputting the time-divided video images together with video images of programs of normal channels.

According to a third aspect of the present invention, an apparatus for receiving a TV broadcasting program which receives, decodes and displays one digitally encoded data or more so that video images of programs of a plurality of channels for promotion are displayed on a screen by screen division, comprises a video image extracting means for decoding the received data, selecting and extracting only a video image of a program of a prescribed channel among the decoded data, and a video image display position movement means for moving a display position of a video image so that the video image of a program of the extracted channel is displayed in a prescribed position on a divided screen.

According to a fourth aspect of the present invention, an apparatus for receiving a TV broadcasting program which receives, decodes and displays data which is transmitted, the data being a digitally encoded video image of a program for promotion which is transmitted by time division through each channel, comprises a video image extracting means for decoding the received data, selecting and extracting only a video image of a program of a prescribed channel among the decoded data, and a video image display position movement means for moving a position of a video image so that the video image of a program of the extracted channel is displayed in a prescribed position on a divided screen.

According to a fifth aspect of the present invention, an apparatus for receiving a TV broadcasting program which receives one digitally encoded data or more so that video images of programs of a plurality of channels for promotion are displayed on a screen by screen division, and receives program character information with respect to each program, and decodes and displays the data and the program character information, comprises a video image extracting means for decoding the received data, selecting and extracting only a video image of a program of a prescribed channel among the decoded data, a video image display position movement means for moving a position of a video image so that the video image of a program of the extracted channel is displayed in a prescribed position on a divided screen, and a program character information synthesizing means for synthesizing program character information indicating a content corresponding to the video image displayed in a prescribed position by the video image display position movement means with the video image to display the same on a screen.

According to a sixth aspect of the present invention, an apparatus for receiving a TV broadcasting program which receives data which is transmitted, the data being a digitally encoded video image of a program for promotion which is transmitted through each channel by time division, and receives program character information with respect to each program, and decodes and displays the data and the program character information, comprises a video image extracting means for decoding the received data, selecting and extracting only a video image of a program of a prescribed channel, a video image display position movement means for moving a position of a video image so that the video image of a program of the extracted channel is displayed in a prescribed position on a divided screen, and a program character information synthesizing means for synthesizing program character information indicating a content corresponding to the video image displayed in a prescribed position by the video image display position movement means with the video image to display the same on a screen.

As described above, according to the present invention, in the broadcasting station, program video image information of a plurality of programs for promotion is digitally encoded and transmitted through a promotion channel as a channel, and in the receiver, program video image information of a program of a channel corresponding to a program specified by the viewer is extracted from the promotion channel transmitted as the multi screen and displayed with display position moved on the screen as required. Therefore, the content of the promotion channel edited in the transmission station can be edited and displayed, specified by the viewer as the viewer likes, and information of a desired program among many programs can be obtained with efficiency, so that efficiency in choosing a program is increased.

In addition, the video image of the program for each

one promotion channel is transmitted by time division as a stream through the promotion channel, and only a program of a channel specified by the viewer is extracted from the promotion channel transmitted by time division and displayed moving a display position so that a video image of a specified channel is displayed in a specified position on a screen in displaying the same by screen division. Therefore, contents of the promotion channel edited in the broadcasting station can be edited and displayed, specified by the viewer, and information of a desired program among many programs can be obtained with efficiency, so that efficiency in choosing a program is increased. In addition, a plurality of streams of the video image and the sound can be transmitted through a promotion channel. Therefore, more program information about a program can be provided.

Further, character information corresponding to a video image of each program for promotion is synthesized with the video image and displayed, thereby additional information for each program can be provided using character, so that service can be improved.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram for illustrating an apparatus for transmitting a TV broadcasting program according to an embodiment 1 of the present invention.

Figure 2 is a block diagram for illustrating an apparatus for receiving a TV broadcasting program according to the embodiment 1 of the present invention.

Figure 3 (a) and 3(b) are diagrams for explaining a display status of program information in a video image display means of an apparatus for receiving TV broadcasting programs according to an embodiment 2 of the present invention.

Figure 4 is a block diagram for illustrating an apparatus for transmitting TV broadcasting programs according to the embodiment 2 of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[Embodiment 1]

Figure 1 is a block diagram illustrating an apparatus for transmitting TV broadcasting programs according to an embodiment 1 of the present invention. In figure 1, reference characters 1a-1n designate analog video input signals in n channels for promotion and reference characters 2a-2n designate n sound input signals corresponding to the analog video input signals in the n channels, where a stream ID corresponding to each sound is included. Reference characters 3a-3n designate n frame reducing means provided correspondingly to the analog video image input signals 1a-1n, and in the frame reducing means, for example, frame reducing processing in each frame is performed to reduce data which is to be output to the next stage. Reference numeral 4 designates a multi screen synthesizing

means for synthesizing each video signal by receiving an output of each frame reducing means 3a-3n and dividing a screen into a plurality of segments so that an input program video image of each program for promotion is displayed as program video image information. Reference numeral 5 designates a video image 1 system/sound n system input encoder for receiving an output of the multi screen synthesizing means 4 and the n sound input signals, and in MPEG 16 programs can be managed at its most. A multi screen producing section 100a which produces one multi screen comprises components described-above. Actually, a plurality of multi screen producing sections (100a-100n) are provided, by which n multi screens can be produced.

Reference characters 6a-6n designate encoders provided correspondingly to a plurality of analog video input signals in normal broadcasting and sound signals in normal broadcasting and each set of video signal and sound signal are input to the encoders, respectively. Reference numeral 7 designates a multiplexing means for receiving outputs of the n multi screen producing means 100a-100n, outputs of the encoders 6a-6n, and service information (SI), as inputs and outputting a transport stream 8. The SI is supplied with program character information corresponding to each promotion channel, corresponding information between a video image position and a sound of each program on multi screen in the promotion channel, and information as to correspondence between program video image information/sound and the program character information, digitally encoded. The SI is included in the transport stream 8 as a stream of service information, to be transmitted.

Figure 2 is a block diagram illustrating an apparatus for receiving a TV broadcasting program according to the embodiment 1. In figure 2, reference numeral 9 designates an antenna for receiving the transport stream 8 which is transmitted in radio waves. Reference numeral 10 designates a tuner for selecting a frequency to receive radio waves of digital broadcasting, decoding the same into digital signals, and conducting error correction.

Reference numeral 11 designates a signal separating means for selecting the promotion channel or the normal program among a plurality of channels, separating and extracting program video image information, sound signals and program character information in the promotion channel, and separating and extracting a video image and a sound in the normal program, from digital signals received by the tuner 10, by selecting a packet identifier (PID) in the MPEG. Reference numeral 12 designates a sound reproducing means for decoding and reproducing a sound digitally compressed by the MPEG or the like. Reference numeral 13 designates a program information management means for obtaining and managing program character information extracted by the signal separating means 11. Reference numeral 14 designates a video image reproducing means for decoding and reproducing the video image compressed

by the MPEG or the like. Reference numeral 15 designates a video image allocating means for allocating selected program video image information in a specified range as required, enlarging/reducing the allocated program video image information to specified-sized one, and writing the enlarged/reduced video image information into a frame buffer 18 for storing data output from the video image allocating means 15 so that it is moved to a specified location. Reference numeral 16 designates a multi screen management means for controlling each operation of the signal separating means 11, the video image reproducing means 14, the video image allocating means 15 and the video image synthesizing means 19 mentioned later. Reference numeral 19 designates a video image synthesizing means for synthesizing the video image of the frame buffer 18 with a graphic such as a cursor or text (program character information). Reference numeral 20 designates a sound outputting means for outputting a sound reproduced by the sound reproducing means, such as a speaker. Reference numeral 21 designates a video image display means for displaying the video image synthesized by the video image synthesizing means 19, such as CRT (color brown tube).

A description is given of an operation.

In the apparatus for transmitting a TV broadcasting program illustrated in figure 1, i.e., transmission side, n analog video signal inputs 1a-1n for promotion are frame-reduced in each frame by frame reducing means 3a-3n, respectively with a frame rate changed to approximately 10 frames/second, for example, and input to the multi screen synthesizing means 4 as the program video image information. In the multi screen synthesizing means 4, a plurality of video images of programs for promotion are respectively reduced and synthesized so that they are displayed divided into a prescribed number. For example, in case of twelve channels, a screen is divided into twelve and displayed.

The encoder 5 receives an output of the multi screen synthesizing means 4 and n sound input signals 2a-2n corresponding to the n analog video signal inputs for promotion, and compresses and encodes the same into a digital video image and sound.

On the other hand, the analog video signal inputs and sound input signals in the plurality of normal channels are respectively input to encoders 6a-6n provided in each program, respectively compressed and encoded into a digital video image and sound therein, and input to the multiplexing means 7 together with the output of the encoder 5, to be collected into a stream and output as the transport stream 8. At this time, corresponding information between display position of the video image of the program for each promotion and sound signals in each program, program character information in each program for each promotion, and corresponding information between the character information and the video image/sound of the program for each promotion are digitally encoded and are output as a stream of service information and as a transport

stream 8. Thereafter, addition of an error correcting code and modulation are performed for the stream, which is transmitted in radio waves.

In the receiver's side illustrated in figure 2, a frequency is selected among broadcasting signals received by the antenna 9, by the tuner 10, to receive radio waves in digital broadcasting, and decoding and error correcting processing are performed. By the signal separating means 11, bit stream of (EPG) channel and SI are selected among digital signals (transport stream) received by the tuner 10, and program video image information/sound signals and program character information are separated and extracted by selecting PID in the MPEG based on the instruction from a multi screen management means 16 mentioned later. Program video image information in the multi screen corresponding to a video image stream ID specified by the multi screen management means 16 is reproduced by the video image reproducing means 14.

The multi screen management means 16 controls an operation of the video image allocating means 15 based on an input of remote controller of the viewer, and decides a program specified using a remote control inputting means 17 by the viewer referring to screen position information which has been transmitted as the SI. The video image allocating means 15 allocates only program video image information of the corresponding program, referring to the corresponding program video image information of program video image information in multi screen which has been reproduced by the video image reproducing means 14, and outputs the allocated video image information to the frame buffer 18 in the next stage. At this time, the video image allocating means 15 performs processing such as allocating program video image information in a specified range or reducing/enlarging the same as required. Allocation of the program video image information is performed by writing data into prescribed addresses in the frame buffer 18 based on the instruction from the multi screen management means 16 so that the allocated video image is displayed in a position on a screen specified by the viewer later.

The program character information separated by the signal separating means 11 is sorted/rearranged by the program information management means 13 and transmitted to the multi screen management means 16, and then synthesized with a video image by the video image synthesizing means 19 mentioned later.

Thus, program video image information of each program processed by the video image allocating means 15 is sequentially stored in the frame buffer 18 in the next stage, where a plurality of program video image information specified through the remote control inputting means 17 is stored.

On completion of storage of data of all program video image information specified by one screen or the stream ID, the data is synthesized with a graphic such as program character information or a cursor. At this time, program video image information of a plurality of

programs stored in the frame buffer 18 and program character information sorted/rearranged by the program information management means 13 are checked based on information which has been transmitted as service information, and respectively corresponding program video image information and program character information are correlated and synthesized. Figure 3(a) is a diagram illustrating a state in which program video image information processed described above is displayed on a screen 30 in the video image display means 21. The screen 30 is divided into twelve by a display cell 31 and program information of programs 1, 2, 6, 4 is displayed correspondingly to display cells 31a-31d disposed in upper left to right direction on the screen. Reference numeral 32 designates a rectangular cursor displayed in the display cell 31a. The cursor 32 can be moved to an arbitrary position on the screen in accordance with a signal input from the remote control means 17. A sound outputting means 20 operates together with the cursor 32 to reproduce a sound corresponding to program information of a selected program. Channels are switched by selecting one of the cells in the video image display means 21 (the screen 30) and pressing a full screen display button provided in a remote controller (not shown), and a program or a program reserve screen of the selected cell or the like is displayed over the screen 30. As illustrated in figure 3(b), program video image information 310 and program character information 311 are synthesized and displayed on each display cell 31.

Operations in accordance with the embodiment 1 are described. In the broadcasting station, program video image information and sounds of a plurality of programs are digitally encoded according to the MPEG standard to make them a promotion channel for one channel, and at least one promotion channel or more and video images and sounds of a plurality of normal programs are multiplexed and transmitted as the transport stream. In the receiver side, program video image information of a program included in a channel corresponding to a program specified by the viewer is extracted from one promotion channel or more transmitted as the multi screen referring to the packet ID of a stream and a position on the screen and a display position on the screen is moved as required. Therefore, contents of the promotion channel edited in the transmission station can be edited and displayed, specified by the viewer in the receiver and information of a desired program among many programs can be obtained with efficiency, so that efficiency in choosing a program is increased. Further, more information can be provided by transmitting the character information simultaneously as program information and synthesizing the same with program video image information of a corresponding program, followed by display.

[Embodiment 2]

A description is given of an apparatus for transmit-

ting TV broadcasting programs according to an embodiment 2. In the embodiment 1, synthesis of program video image information of a plurality of programs on a screen (multi screen) as the promotion channel in the broadcasting station is transmitted. In the embodiment 2, individual program information is transmitted by time division as a stream in a promotion channel.

In figure 4, outputs of program information (video image/sound) for promotion of each program are sequentially switched by the video image allocating means 40 and are input sequentially to the encoder 5 in the next stage in such a manner that the stream ID is not input at the same time, and compressed and encoded into a digital video image and sound therein. The encoder 5 can manage sixteen programs at its most in case of MPEG.

A promotion stream producing means 400a for producing a multi screen comprises the components described above. Actually, a plurality of promotion stream producing means (400a-400n) are provided and can produce n promotion streams.

The multiplexing means 7 multiplexes n promotion streams output from the n promotion stream producing means 400a-400n and a plurality of normal programs and outputs the multiplexed streams and programs as a transport stream 8. At this time, program character information in each program for each promotion and corresponding information between the character information and video image/sound of the program for each promotion are digitally encoded and output as a stream of service information and simultaneously as the transport stream 8. Thereafter, addition of an error correcting code and modulation are performed for the stream, which is transmitted in radio waves.

On the other hand, the receiver basically comprises constructions as illustrated in figure 2. A promotion channel is selected among the transport stream 8 which has been transmitted and program video image information/sound signal and program character information included in program information of a program to be displayed as the multi screen prespecified by the viewer using the remote control inputting means 17 are respectively separated and extracted by the signal separating means 11 in figure 2. The program video image information is reproduced by the video image reproducing means 14 based on the instruction from the multi screen management means 16. Also, the program video image information is reduced/enlarged by the video image allocating means 15 as required and data is written into prescribed addresses in the frame buffer 18 so that the allocated video images will be displayed in a position on a screen specified by the viewer.

The video image synthesizing means 19 checks the program video image information obtained described above with the program character information output through the multi screen management means 16 using the packet ID of the stream and the stream ID in the MPEG as in the embodiment 1 and synthesizes the same so that they are displayed in the video image dis-

play means 21 as illustrated in figure 3(b).

In accordance with the embodiment 2, the video image and the sound of each program are respectively transmitted by time division as a stream in the promotion channel and the stream ID is assigned to each program in transmission, thereby contents of the promotion channel can be edited and displayed, specified by the viewer in the receiver and information of a desired program among many programs can be obtained with efficiency, so that efficiency in selecting a program is increased. In addition, a plurality of streams of the video image and the sound can be respectively transmitted through one promotion channel. Therefore, more program information about a program can be provided.

In the embodiments described above, a frame-reduced motion picture is employed as program video image information which is transmitted. Alternatively, a still picture may be employed, and can be transmitted as a motion picture when the still picture has a large transmission capacity.

The frame reducing means is provided in the preceding stage of the multi screen synthesizing means 4. Alternatively, one frame reducing means may be provided in the next stage of the multi screen synthesizing means 4. Also, when there is no limit on the transmission capacity, the frame reducing means may omitted.

A description has been given of a case where one screen is divided into twelve to display the program information. Alternatively, when program information not less than division number on a screen is demanded, a plurality of program information screens may be prepared in page specified system. In this case, preferably, the frame buffer 18 has a page-sized capacity, thereby high speed screen switching can be realized.

In each embodiment described above, program video images for promotion are employed to constitute the promotion channel. Alternatively, each program which is currently broadcasted is employed to constitute the promotion channel.

Claims

1. An apparatus for transmitting a TV broadcasting program comprising:

a video image synthesizer for synthesizing video images so that the video images of a plurality of channels for promotion are displayed on a screen by screen division;
an encoder for digitally encoding the synthesized one video image or more; and
a multiplexer for multiplexing and outputting the digitalized video images for promotion and digitally encoded programs of normal channels.

2. An apparatus for transmitting a TV broadcasting program comprising:

a multiplexer for time-dividing video images of

programs of a plurality of channels for promotion, multiplexing and outputting the time-divided video images and video images of programs of normal channels.

5

3. An apparatus for receiving a TV broadcasting program which receives, decodes and displays one digitally encoded data or more so that video images of programs of a plurality of channels for promotion are displayed on a screen by screen division comprising:

10

a video image extracting means for decoding the received data, selecting and extracting only a video image of a program of a prescribed channel among the decoded data; and
a video image display position movement means for moving a display position of a video image so that the video image of the program of the extracted channel is displayed in a prescribed position on a divided screen.

15

20

4. An apparatus for receiving a TV broadcasting program which receives, decodes and displays data which is transmitted, the data being a digitally encoded video image of a channel for promotion which is transmitted through each channel by time division, comprising:

25

a video image extracting means for decoding the received data, selecting and extracting only a video image of a program of a prescribed channel among the decoded data; and
a video image display position movement means for moving a display position of a video image so that the video image of the program of the extracted channel is displayed in a prescribed position on a divided screen.

30

35

5. An apparatus for receiving a TV broadcasting program which receives one digitally encoded data or more so that video images of programs of a plurality of channels for promotion are displayed by screen division on a screen and receives program character information with respect to each program, and decodes and displays the data and the program character information, comprising:

40

45

a video image extracting means for decoding the received data, selecting and extracting only a video image of a program of a prescribed channel among the decoded data,
a video image display position movement means for moving a display position of a video image so that the video image of the program of the extracted channel is displayed in a prescribed position on a divided screen; and
a program character information synthesizing means for synthesizing program character

55

information indicating a content corresponding to a video image displayed in a prescribed position by the video image display position movement means with the video image, to be displayed on the screen.

6. An apparatus for receiving a TV broadcasting program which receives data which is transmitted, the data being a digitally encoded video image of a program for promotion which is transmitted through each channel by time division, and receives program character information with respect to each program, and decodes and displays the data and the program character information, comprising:

a video image extracting means for decoding the received data, selecting and extracting only a video image of a prescribed channel among the decoded data;

a video image display position movement means for moving a display position of a video image so that the video image of the program of the extracted channel is displayed in a prescribed position on a divided screen; and
a program character information synthesizing means for synthesizing program character information indicating a content corresponding to a video image displayed in a prescribed position by the video image display position movement means with the video image, to be displayed on the screen.

7. The apparatus for receiving a TV broadcasting program according to any one of the preceding claims 1 to 6, further comprising a rectangular cursor to be displayed in a display cell being a region in which video images of programs of a plurality of channels for promotion are displayed on a screen by screen division, the cursor being moved to an arbitrary position on the screen by external input signals to select a prescribed display cell, thereby reproducing voice corresponding to program information of a program of the selected display cell.

Fig.1




Fig.2




Fig.3 (a)




Fig.3 (b)





Fig.4





Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 805 591 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
16.06.1999 Bulletin 1999/24

(51) Int. Cl.⁶: **H04N 7/12**

(43) Date of publication A2:
05.11.1997 Bulletin 1997/45

(21) Application number: **97107041.2**

(22) Date of filing: **29.04.1997**

(84) Designated Contracting States:
DE FR GB

(30) Priority: **02.05.1996 JP 11167696**
28.01.1997 JP 1363797

(71) Applicant:
MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.
Kadoma-shi, Osaka 571-8501 (JP)

(72) Inventors:
- **Aoki, Norio**
Hirakatashi, Koganeno 2-16-5, 573 (JP)
- **Yoneda, Yasushi**
Ikedashi, Fushiodai 2-9-1 2-193, 563 (JP)

(74) Representative:
Kügele, Bernhard et al
NOVAPAT INTERNATIONAL SA,
9, Rue du Valais
1202 Genève (CH)

(54) **Apparatus for transmitting television broadcasting program and apparatus for receiving television broadcasting program**

(57) An apparatus for transmitting a TV broadcasting program comprises a video image synthesizer for synthesizing video images so that the video images of a plurality of channels for promotion are displayed on a screen by screen division; an encoder for digitally encoding the synthesized one video image or more; and a multiplexer for multiplexing and outputting the digitalized video images for promotion and digitally encoded programs of normal channels.

EP 0 805 591 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 97 10 7041

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 95 28794 A (PHILIPS ELECTRONICS NV ;PHILIPS NORDEN AB (SE)) 26 October 1995	1,3	H04N7/12
Y	* page 3, line 23 - page 4, line 8; figure 1 *	7	
X	* page 5, line 21 - line 28; figure 4 *	2,4	
A	* page 6, line 18 - page 8, line 32 *	5,6	
Y	EP 0 598 576 A (TOKYO SHIBAURA ELECTRIC CO) 25 May 1994	7	
A	* column 6, line 47 - column 7, line 19 *	1-4	
A	WO 95 28795 A (PHILIPS ELECTRONICS NV ;PHILIPS NORDEN AB (SE)) 26 October 1995	3,4	H04N
	* page 7, line 7 - page 8, line 11; figure 7 *		
A	WO 95 15646 A (THOMSON CONSUMER ELECTRONICS ;STEYER JEAN MARIE (FR); MAETZ YVES () 8 June 1995	1-6	
	* the whole document *		
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
THE HAGUE		23 April 1999	Beaudoin, O
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/92 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 10 7041

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

23-04-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9528794 A	26-10-1995	AU 686355 B	05-02-1998
		AU 2082195 A	10-11-1995
		AU 700272 B	24-12-1998
		AU 2082295 A	10-11-1995
		BR 9507363 A	18-11-1997
		CA 2187796 A	26-10-1995
		CN 1149953 A	14-05-1997
		CN 1149950 A	14-05-1997
		EP 0755604 A	29-01-1997
		EP 0775413 A	28-05-1997
		WO 9528795 A	26-10-1995
		JP 9512147 T	02-12-1997
		JP 9512148 T	02-12-1997
		US 5633683 A	27-05-1997
EP 0598576 A	25-05-1994	JP 6351017 A	22-12-1994
		JP 6165178 A	10-06-1994
		CA 2102470 A	17-05-1994
		DE 69321322 D	05-11-1998
		EP 0853428 A	15-07-1998
		KR 136250 B	01-06-1998
		US 5537153 A	16-07-1996
WO 9528795 A	26-10-1995	AU 686355 B	05-02-1998
		AU 2082195 A	10-11-1995
		AU 700272 B	24-12-1998
		AU 2082295 A	10-11-1995
		BR 9507363 A	18-11-1997
		CA 2187796 A	26-10-1995
		CN 1149953 A	14-05-1997
		CN 1149950 A	14-05-1997
		EP 0755604 A	29-01-1997
		EP 0775413 A	28-05-1997
		WO 9528794 A	26-10-1995
		JP 9512147 T	02-12-1997
		JP 9512148 T	02-12-1997
		US 5633683 A	27-05-1997
WO 9515646 A	08-06-1995	FR 2713427 A	09-06-1995
		EP 0694242 A	31-01-1996
		JP 8506469 T	09-07-1996
		US 5822014 A	13-10-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82